

SPECIFICATIONS

FUNCTION:
1P2T ON-ON

RATINGS:
5A 125VAC/28VDC, 2A 250VAC

CONTACT RESISTANCE:
Max. 10mΩ


INSULATION RESISTANCE:
1,000MΩ Min.

DIELECTRIC STRENGTH:
1,500VAC

ELECTRICAL LIFE:
30,000 Cycles

OPERATING TEMPERATURE:
-30°C to 85°C

SCHEMATIC



MATERIALS

BODY:
Dially Phthalate (DAP), UL 94V-0

BODY COVER:
Stainless Steel

ACTUATOR:
Nylon

CONTACTS:
Silver Plated Coin Silver

ELECTRICAL TERMINALS:
Silver Plated Copper Alloy

COLORS

BODY:
Red

BODY COVER:
Metallic

ACTUATOR:
Black

	P.O. Box 25110 Portland, OR 97298	LAST REVISION: MAR. 16, 2005
	DRAWING NUMBER: 17-1101-M2S3AV2QE2.dwg	
1101-M2S3AV2QE2		

UNLESS OTHERWISE SPECIFIED,
DIMENSIONS ARE IN INCHES [MILLIMETERS]
TOLERANCES ARE:

DEC .X±0.2	ANG ± 1°
.XXX±0.008	DRAWING NOT TO SCALE