




SCHEMATIC



POSITION 1  
(MOMENTARY)



POSITION 2  
(MAINTAINED)



POSITION 3  
(MOMENTARY)

SPECIFICATIONS

FUNCTION:

1P2T (ON)-OFF-(ON)

RATINGS:

20A 125VAC [cULus]

12A 250VAC [cULus]

1.5HP 125/250VAC [cULus]

OPERATING LIFE:

6,000 Cycles [cULus]

CONTACT RESISTANCE:

Initial: 50mΩ Max. at 50VAC

INSULATION RESISTANCE:

800MΩ Min. at 500VDC

DIELECTRIC STRENGTH:

1,500VAC for 1 Minute

TEMPERATURE:

Operating: -20°C to 85°C

APPROVALS:



MATERIALS

BODY:

Phenolic, UL94 V-0

ACTUATOR:

Nickel Plated Brass

BUSHING:

Nickel Plated Brass

HOUSING:

Stainless Steel


CONTACTS:

Silver Alloy



TERMINALS:

Brass

SUGGESTED PANEL CUTOUT



ALTERNATE PANEL CUTOUT



UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [MILLIMETERS] TOLERANCES ARE:	
DEC .X±0.2	ANG ± 1°
.XXX±0.008	DRAWING NOT TO SCALE
DRAWN BY: KEITH MARCOE	

LAMB INDUSTRIES P.O. Box 25110  
Portland, OR 97298

LAST REVISION:  
APR 01, 2007

DRAWING NUMBER: 34-ST16DD00.dwg

ST16DD00