


SUGGESTED PANEL CUTOUT



PANEL THICKNESS	X
0.030~0.049 [0.75~1.25]	0.756 [19.2]
0.049~0.079 [1.25~2.00]	0.764 [19.4]
0.079~0.118 [2.00~3.00]	0.772 [19.6]

SPECIFICATIONS

FUNCTION:
2P1T OFF-ON

RATINGS:
16A 125VAC, 10A 250VAC [UL]
1/3HP 125-250VAC T105 [UL]
12(4)A 250VAC 1E4 [European]
6(4)A 250VAC 5E4 [European]

CONTACT RESISTANCE:
Max. 30mΩ

INSULATION RESISTANCE:
100MΩ at 500VDC

WITHSTAND VOLTAGE:
1500VAC For 1 Minute

ELECTRICAL LIFE:
50,000 Cycles

APPROVALS:



MATERIALS

BODY:
Polyamide 6/6

ROCKER:
Polyamide 6/6

CONTACTS:
Silver Plated Copper

ELECTRICAL TERMINALS:
Silver Plated Copper

COLORS AND MARKINGS

BODY:
Black

ROCKER:
Black

MARKINGS:
I/O Vertical

MARKING COLOR:
White

0.512+0.004/-0.000 [13.0+0.1/-0.0]

LAMB INDUSTRIES P.O. Box 25110 Portland, OR 97298

LAST REVISION:
JULY 15, 2003

UNLESS OTHERWISE SPECIFIED,
DIMENSIONS ARE IN INCHES [MILLIMETERS]
TOLERANCES ARE:
DEC .X±0.2 ANG ± 1°
.XXX± 0.008 DRAWING NOT TO SCALE

DRAWING NUMBER: 38-RA812C1121.dwg

RA812C1121